

KODAK XTOL Developer



DESCRIPTION

KODAK XTOL Developer is a two-part powder developer for processing Kodak and other manufacturers' normally exposed, pushed, or pulled black-and-white films. It offers full emulsion speed and easy mixing, and can be used as both a developer and a replenisher in a variety of equipment, from small tanks (8 to 64 fluidounces), trays, or rotary tubes to high-volume processors.

FEATURES	BENEFITS
<ul style="list-style-type: none"> Ascorbic acid-based black-and-white film developer 	<ul style="list-style-type: none"> Very high image quality at full emulsion speed
<ul style="list-style-type: none"> No hydroquinone 	<ul style="list-style-type: none"> Convenient, room-temperature mixing for immediate use
<ul style="list-style-type: none"> Two-part powder 	<ul style="list-style-type: none"> Quick, easy mixing
<ul style="list-style-type: none"> One solution for both developer and replenisher 	<ul style="list-style-type: none"> Versatility Simplified mixing and storage procedures
<ul style="list-style-type: none"> Excellent keeping properties 	<ul style="list-style-type: none"> Excellent shelf life (one year after mixing when stored in full bottles) High resistance to breakdown from oxidation during storage or in replenished processes Less waste
<ul style="list-style-type: none"> Robust, abuse-tolerant, clean-working solution 	<ul style="list-style-type: none"> Stable performance across a wide range of temperatures, dilutions, and agitation methods Long, stable solution life Less frequent tank cleaning
<ul style="list-style-type: none"> Contrast Index similar to that produced by other developers 	<ul style="list-style-type: none"> Negatives with printing characteristics like those processed in other general-purpose developers
<ul style="list-style-type: none"> Excellent emulsion speed with normal and push processing 	<ul style="list-style-type: none"> Enhanced shadow contrast and improved highlight detail with some films
<ul style="list-style-type: none"> Fine grain and high sharpness 	<ul style="list-style-type: none"> Enhanced sharpness, especially with dilution Enlargeability of negatives 10 percent greater with equivalent sharpness and grain (image quality)

SIZES AVAILABLE

Sizes and catalog numbers may differ from country to country. See your dealer who supplies Kodak Professional products.

To Make	CAT No.
1 litre	888 8182
5 litres	875 1752
50 litres	818 4517

MIXING

Note: Observe precautionary information on the containers and in the Material Safety Data Sheets.

For this amount of developer:	Start with this amount of water:
1 litre	750 mL
5 litres	4 litres
50 litres	40 litres

1. Start with an amount of water that is approximately 75 percent of the total volume indicated on the package. See the table above. The water should be at normal room temperature, about 65 to 85°F (18 to 30°C).
2. With stirring, slowly add Part A. Stir until the powder is completely dissolved. At this point, the solution may appear somewhat tawny or copper-colored. This is normal.
3. Continue stirring, and slowly add Part B. Stir until the powder is completely dissolved. The coppery tint will clear from the solution as you add Part B.
4. Add water to bring the final solution to 1, 5, or 50 litres.
5. Stir until the solution is uniform.

If correctly mixed, the specific gravity of the working tank solution is 1.085 ± 0.003 measured at $77 \pm 0.5^\circ\text{F}$ ($25 \pm 0.3^\circ\text{C}$) at $\text{pH } 8.2 \pm 0.05$.

STORAGE OF MIXED SOLUTIONS

Store mixed KODAK XTOL Developer in full, tightly closed containers or in a replenisher tank with a floating lid. To maintain shelf life, minimize the amount of air space in the storage container. Partially filled containers allow oxidation of the solution.

STORAGE LIFE OF UNUSED SOLUTIONS		
In Full, Tightly Closed Container	In Partially Filled, Tightly Closed Container	In Replenisher Tank with Floating Lid
Approximately 1 year	At least 2 months	Indefinitely if new solution is added to replace that used by the processor

SMALL-TANK, TRAY, AND ROTARY-TUBE PROCESSING

See the appropriate table on the following pages for starting-point recommendations for specific films.

Note: Some rotary-tube processors allow replenishment of the developer. See “Replenishment” for more information.

Using Full-Strength Developer

Choose the appropriate table for development times and temperatures for using fresh, full-strength KODAK XTOL Developer. The capacity of the full-strength developer with normal, unreplenished processing is approximately 15 rolls of 135-36 or 120 film (or the equivalent of 80 square inches [516 square centimetres]) per litre, with time compensation.

Time Compensation. To process the maximum number of rolls of film per litre of full-strength XTOL Developer, use time compensation according to the table below. Discard the developer after you process 15 rolls of film per litre.

Time Compensation for KODAK XTOL Developer		
Film Size	Number of Rolls (per litre)	Development-Time Increase
135-36 or 120 rolls (80 square inches* or equivalent)	1 to 5	Use normal development time
	6 to 10	Increase normal development time by 15 percent
	11 to 15	Increase adjusted development time by 15 percent

* 80 square inches = one 135-36 or 120 roll, four 4 x 5-inch sheets, or one 8 x 10-inch sheet; 160 square inches = one 220 roll.

Minimum Solution Volume. The volume of full-strength KODAK XTOL Developer needed to cover the film will depend on the size of your tank or tray or the design of your rotary-tube processor.

Using Diluted Developer

Choose the appropriate development time and temperature table for starting-point recommendations for specific films in small tanks, tray, and rotary tubes.

You can dilute KODAK XTOL Developer 1:1, 1:2, or 1:3 with water (developer:water) for one-shot (single-use) processing. Dilution at 1:1 will provide slightly greater film speed, enhanced sharpness and shadow detail, and slightly more grain. Dilution at 1:3 will generally provide less film speed and shadow detail, with enhanced sharpness and slightly more grain.

Use **diluted developer only once**. Do not replenish or reuse diluted developer.

Minimum Solution Volume. The volume of diluted KODAK XTOL Developer needed to cover the film will depend on the size of your tank or tray or the design of your rotary-tube processor. However, the minimum amount of diluted developer needed to cover the film may not contain enough active ingredients to develop the film fully in the recommended time. We recommend always starting with at least 100 mL (3.5 fluidounces) of full-strength developer to prepare the diluted solution for each 135-36 or 120 roll (or the equivalent of 80 square inches [516 square centimetres]). For example, for a 1:3 dilution, this would produce about 400 mL (14 fluidounces) of solution. This is the minimum amount per roll, even though a smaller volume may be enough to cover the film.

Note: If your water supply is exceptionally hard (above 200 ppm of CaCO₃), you may need to use conditioned water to avoid cloudiness when you mix higher dilutions. Contact your water authority for information on the water in your area.

Using Seasoned Developer

To use seasoned XTOL Developer in an unreplenished manual process, see the appropriate development time and temperature table for starting-point recommendations for specific films.

You can take the solution from the developer overflow line or the working tank of an in-control replenished process. You can also “pre-season” fresh XTOL Developer by adding 6.5 mL of KODAK Developer Starting Solution (CAT 146 6382) per litre of developer. Or use 1 mL of KODAK EKTACHROME R-3 First Developer II Starter (CAT 869 9795 [U.S. and Australia] or CAT 524 0007 [Europe]) per litre of XTOL Developer.

Agitating Rolls in Small Tanks

The times given for small-tank processing in the development time and temperature tables are based on the following agitation procedure:

1. Fill the empty tank with developer.
2. Start the timer. In the dark, carefully place the loaded reel into the developer solution.
3. Quickly attach the top to the tank. Firmly tap the bottom of the tank against the work surface from a height of approximately 1 inch (2.5 cm) to dislodge air bubbles from the surface of the film. Air bubbles can interfere with development and produce low-density circles on the film.
4. Provide initial agitation of up to 5 cycles, depending on your results. For KODAK T-MAX Professional Films, provide initial agitation of 5 to 7 cycles in 5 seconds. For an invertible tank, one cycle consists of rotating the tank upside down and then back to the upright position. For a noninvertible tank, one cycle consists of sliding the tank back and forth over a 10-inch (25.4 cm)

distance. With tanks that have a handle for turning the reel, rotate the reel back and forth gently through about one-half turn at a rate of one cycle per second during initial and subsequent agitation. Steps 2 through 4 will take approximately 7 to 20 seconds, depending on the type of tank.

5. Let the tank sit for the remainder of the first 30 seconds.
6. After the first 30 seconds, agitate for 5 seconds at 30-second intervals. Agitation should consist of 2 to 5 cycles, depending on the contrast you need and the type of tank.

Agitating Sheet Film in Trays

To process a single sheet:

1. Fill a tray with water that is at the same temperature as the developer.
2. Slip the film into the developer. Rock the tray immediately to make sure the film is covered with solution.
3. Agitate the film by first raising the left side of the tray about 3/4 inch (2 cm). Lower it smoothly, and then immediately raise and lower the side nearest to you. Next, raise and lower the right-hand side, then the near side again. This agitation cycle takes about 8 seconds.
4. Agitate continuously throughout the development time.
5. At the end of the development time, drain the sheet for a few seconds and transfer it to the stop bath. To avoid contaminating the developer with stop bath, use one hand for lifting the sheet from the developer and the other hand for placing it in the stop bath.

To process two to six sheets together:

1. Fill a tray with water that is at the same temperature as the developer.
2. Immerse the sheets one at a time, emulsion side up, in the tray of water. Make sure that each sheet is covered with water before inserting the next one. Agitate by moving the bottom sheet to the top of the stack every few seconds. Go through the stack twice. Be careful that the corners of the sheet you are handling do not scratch the sheet under it.
3. Take the bottom sheet out of the tray of water, drain it for a few seconds, and place it in the developer, emulsion side up. Make sure that the sheet is covered with developer. Transfer the rest of the sheets to the developer in the same way. Interleave the stack, from bottom to top, until development is complete.
Note: When you use interleaving agitation, go through the stack of sheets completely. Rotate the first sheet in the developer 180° from the rest of the stack so that the notch is at the opposite end. This identifies it as the first sheet; be sure that it is the first sheet you remove from each solution.
4. At the end of the development time, transfer the sheets to the stop bath one at a time in the order they were placed in the developer. Drain each sheet for the same time that the sheets were drained in Step 3 when placed

in the developer. To avoid contaminating the developer with stop bath, use one hand for lifting the sheets from the developer and the other hand for placing them in the stop bath.

Final Steps in Small-Tank, Tray, and Rotary-Tube Processing

Step	Time	Comments
Stop Bath	30 seconds	Agitate continuously.
Fixer	Twice as long as it takes the film to clear (lose its milky appearance); see the specific film or fixer instructions.	Agitate continuously for the first 30 seconds and for 5 seconds at 30-second intervals after that.
Rinse	30 seconds	Rinse the film in the tank under running water.
Hypo Clearing Agent	1 to 2 minutes	Agitate continuously for the first 30 seconds and at 30-second intervals after that.
Wash	5 minutes	Run the wash water at least fast enough to provide a complete change of water in the container in 5 minutes. For rapid washing in a small tank, fill the tank to overflowing with fresh water and then dump it all out. Repeat this cycle 10 times.
PHOTO-FLO Solution	30 seconds to 1 minute	To minimize drying marks, treat the film with KODAK PHOTO-FLO Solution after washing.
Dry	As needed	Dry in a dust-free place.

LARGE-TANK (REPLENISHED) PROCESSING

See the large-tank development time and temperature tables for starting-point recommendations for specific films. For critical applications, run tests to determine the best development time. These recommendations are based on a nitrogen-burst agitation cycle of two seconds at 10-second intervals. Significantly more agitation may require slightly shorter development times; less agitation may require longer times.

If you have a broad film mix that requires a wide variety of development times, you may want to establish a few standard batch cycles, such as 5, 6, 7, 8, 10, and 12 minutes. Then you can assign each film to the nearest batch cycle, based on the recommendations in the tables.

Starting (Preseasoning) a Fresh Working Tank Solution

To start or preseason a fresh working tank solution:

1. Add 6.5 mL of KODAK Developer Starting Solution (CAT 146 6382) per litre of tank volume to the empty developer tank. Or use 1 mL of KODAK EKTACHROME R-3 First Developer II Starter (CAT 869 9795 [U.S. and Australia] or CAT 524 0007 [Europe]) per litre of XTOL Developer.
2. Fill the developer tank with fresh KODAK XTOL Developer solution.
3. Stir or recirculate until the solution is uniform.

If you choose not to preseason the fresh tank, initial development times will be about 10 percent shorter than those in the tables, but times will approach the times in the tables as the tank approaches a steady state.

Converting to KODAK XTOL Developer from Another Developer

Before changing to KODAK XTOL Developer, run several KODAK Black-and-White Film Process Control Strips (CAT 180 2990) through your current in-control process at each of your standard development times. Measure and note the Contrast Index of these strips. Drain and clean the developer tank.

To make a fresh working tank solution, follow the mixing directions above for starting a fresh working tank. Run several more process control strips, adjusting the development time and/or temperature until the process produces Contrast Index results that match your previous Contrast Index results.

For more information, see KODAK Publication No. Z-133E, *Monitoring and Troubleshooting KODAK Black-and-White Film Processes* (CAT 889 4784).

Replenishment

You can replenish this developer in systems that use the full-strength solution (not diluted developer). Use XTOL Developer as a replenisher at a rate of 70 mL for each 135-36 or 120 roll, or the equivalent of 80 square inches (516 square centimetres), of film processed.

You can monitor replenished systems with KODAK Black-and-White Film Process Control Strips (CAT 180 2990). Adjust the replenishment rate up or down in 10 mL increments to keep the process on aim. Allow adequate time for the process to stabilize between replenishment-rate adjustments. Use the lowest replenishment rate that will maintain process control. For more information, see KODAK Publication No. Z-133E, *Monitoring and Troubleshooting KODAK Black-and-White Film Processes* (CAT 889 4784).

System Maintenance

KODAK XTOL Developer is very clean-working, and will rarely need replacement in a properly replenished and maintained process.

Take these steps for routine maintenance:

- Minimize air access to the replenisher tanks. Use floating lids.
- Use a small amount of water to rinse the developer from processor parts left exposed to air after shutdown.
- Replace evaporation losses with water at processor start-up.
- If your processor is equipped with recirculation filters, check them frequently, and change them as needed.

DISPOSAL

Dispose of used developer in accordance with your local regulations. Refer to the Material Safety Data Sheets for more information.

If you have environmental or safety questions about Kodak products or services, contact Kodak Environmental Services at 716-477-3194, between 8 a.m. and 5 p.m. (Eastern time).

Kodak also maintains a 24-hour health hotline to answer questions about the safe handling of photographic chemicals. If you need health-related information about Kodak products, call 1-716-722-5151.

DEVELOPMENT TABLES

The following pages contain tables of starting-point development times and temperatures for developer solutions with and without dilution in small tanks, trays, rotary tubes, and large-tank replenished systems. This information includes processing data for Kodak films as well as for a sampling of other manufacturers' films. For critical applications, run tests to determine the best development time. Data for nominal film speeds are in **bold face** type.

Table No.	Title	Page
Roll Films:		
1	Processing Roll Film with FRESH, FULL-STRENGTH DEVELOPER	6
2	Processing Roll Film in Replenished Systems with FULL-STRENGTH DEVELOPER	10
3	Processing Roll Film with FRESH, DILUTE DEVELOPER	14
4	Processing KODAK Technical Pan Film / 2415 in Small Tanks with FRESH, DILUTE DEVELOPER	18
Sheet Films:		
5	Processing Sheet Film in Trays or Large Tanks with FULL-STRENGTH DEVELOPER	19
6	Processing Sheet Film in Rotary Tubes with FULL-STRENGTH DEVELOPER	20
7	Processing Sheet Film with FRESH, DILUTE DEVELOPER	21

Roll Films

**Important**

Development times shorter than 5 minutes (4 minutes in rotary tubes) may produce unsatisfactory uniformity.

TABLE 1: Processing Roll Film with FRESH, FULL-STRENGTH DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	Small Tanks					Rotary Tubes (with Continuous Agitation)			
				65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)
KODAK PLUS-X Pan / PX / 5062 KODAK PLUS-X 125 Pro	135	32/64	0.52	5 ³ / ₄	4 ¹ / ₂ *	4*	3*	2 ¹ / ₂ *	5	4	3 ¹ / ₄ *	2 ¹ / ₂ *
		125	0.58	6¹/₂	5¹/₄	4³/₄*	3³/₄*	2³/₄*	5¹/₂	4¹/₂	4	3*
		250	0.65	7 ³ / ₄	6 ¹ / ₂	5 ³ / ₄	4 ¹ / ₂ *	3 ¹ / ₂ *	6 ¹ / ₄	5 ¹ / ₂	4 ³ / ₄	3 ¹ / ₂ *
		500	0.75	9 ¹ / ₄	8	7 ¹ / ₄	5 ¹ / ₂	4 ¹ / ₄ *	7 ³ / ₄	6 ¹ / ₂	6	4 ¹ / ₂
		1000	0.85	12 ¹ / ₄	10 ¹ / ₄	9 ¹ / ₄	7 ¹ / ₄	5 ¹ / ₄	10	8	7 ¹ / ₂	6
KODAK PLUS-X Pan Professional / PXP / 6057 KODAK PLUS-X 125 Pro	120/220	32/64	0.52	5 ³ / ₄	4 ¹ / ₂ *	4*	3*	2 ¹ / ₂ *	5	4	3 ¹ / ₄ *	2 ¹ / ₂ *
		125	0.58	6³/₄	5¹/₂	5*	3³/₄	3*	5³/₄	4¹/₂	4	3*
		250	0.65	8	6 ³ / ₄	6	4 ³ / ₄ *	3 ¹ / ₂ *	6 ³ / ₄	5 ¹ / ₂	5	3 ¹ / ₂ *
		500	0.75	11	8 ¹ / ₂	7 ¹ / ₂	5 ³ / ₄	4 ¹ / ₂ *	8 ¹ / ₂	7	6	4 ¹ / ₂
		1000	0.85	16	11 ¹ / ₂	10	7 ³ / ₄	6	11	9	8	6
KODAK VERICHROME Pan / VP / 6041	120	32/64	0.52	6 ¹ / ₄	5	4 ¹ / ₂ *	3 ¹ / ₂ *	2 ¹ / ₂ *	5	4	3 ¹ / ₂ *	2 ¹ / ₂ *
		125	0.58	7¹/₂	6	5¹/₄	4*	3*	6	5	4	3*
		250	0.65	8 ³ / ₄	7	6	4 ³ / ₄ *	3 ¹ / ₂ *	7	6	5	4
		500	0.75	11	8 ¹ / ₂	7 ¹ / ₂	5 ³ / ₄	4 ¹ / ₂ *	8 ¹ / ₂	7 ¹ / ₂	6 ¹ / ₂	5
		1000	0.85	13 ¹ / ₂	11	9 ¹ / ₂	7 ¹ / ₄	5 ¹ / ₂	10 ¹ / ₂	9	8	6
KODAK TRI-X Pan / TX / 5063 KODAK TRI-X 400 Pro	135	100/200	0.52	6 ¹ / ₂	5 ¹ / ₂	5	4*	3 ¹ / ₄ *	5	4 ¹ / ₂	4	3*
		400	0.58	7³/₄	6³/₄	6	4³/₄*	3³/₄*	5³/₄	5	4¹/₂	3¹/₂*
		800	0.65	9	7 ³ / ₄	7	5 ¹ / ₂	4 ¹ / ₄ *	6 ¹ / ₂	5 ¹ / ₂	5	4
		1600	0.75	10 ¹ / ₂	9	8	6 ¹ / ₂	5	8	7	6	5
		3200	0.85	12 ¹ / ₂	10 ¹ / ₂	9 ¹ / ₂	7 ¹ / ₂	5 ³ / ₄	9 ¹ / ₂	8	7	6
KODAK TRI-X Pan / TX / 6043 KODAK TRI-X 400 Pro	120	100/200	0.52	6 ³ / ₄	5 ¹ / ₂	4 ³ / ₄ *	3 ³ / ₄ *	3*	5	4 ¹ / ₄	4	3*
		400	0.58	7¹/₂	6¹/₄	5¹/₂	4¹/₄*	3¹/₂*	6	5	4¹/₂	3¹/₂*
		800	0.65	8 ¹ / ₂	7	6 ¹ / ₄	5	4*	7	5 ³ / ₄	5	4
		1600	0.75	10 ¹ / ₄	8 ³ / ₄	7 ³ / ₄	6	4 ³ / ₄ *	8 ¹ / ₂	7	6 ¹ / ₄	5
		3200	0.85	12	10 ¹ / ₄	9	7	5 ¹ / ₂	10	8	7 ¹ / ₂	6

TABLE 1: Processing Roll Film with FRESH, FULL-STRENGTH DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	Small Tanks					Rotary Tubes (with Continuous Agitation)			
				65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)
KODAK TRI-X Pan Professional / TXP / 6049	120/220	80/160	0.52	6¼	5¼	4¾*	3¾*	3*	5	4	3½*	3*
		320	0.58	7½	6¼	5½	4½*	3½*	5½	4½	4	3½*
		640	0.65	9	7½	6¾	5½	4¼*	6½	5½	5	4
		1250	0.75	11½	9½	8½	6¾	5½	8½	7	6½	5
		2500	0.85	14½	11¾	10½	8½	7	11	9	8½	6½
KODAK T-MAX 100 Professional / TMX / 5052 KODAK T-MAX 100 Pro	135	25/50	0.52	7	5¾	5	4*	3¼*	6	5	4½	3½*
		100	0.58	8	6¾	6	4½*	3¾*	7	6	5¼	4
		200	0.65	9	7¾	7	5¼	4¼*	8	7	6	4½
		400	0.75	10½	9	8	6¼	5	9½	8	7	5½
		800	0.85	12	10½	9½	7¼	6	11½	9	8	6½
KODAK T-MAX 100 Professional / TMX / 6052 KODAK T-MAX 100 Pro	120	25/50	0.52	7	5¾	5	4*	3¼*	6	5	4½	3¼*
		100	0.58	8	6¾	6	4½*	3¾*	7	5¾	5	3¾*
		200	0.65	9	7¾	7	5¼	4¼*	8¼	6¾	5¾	4¼
		400	0.75	10½	9	8	6	5	10	8¼	7	5
		800	0.85	12	10¼	9½	7¼	6	11¾	9½	8¼	6
KODAK T-MAX 400 Professional / TMY / 5053 KODAK T-MAX 400 Pro	135	100/200	0.52	6¾	5¾	5	4*	3¼*	6	5	4½	3½*
		400	0.58	7½	6½	5¾	4½*	3½*	6½	5½	5	4
		800	0.65	8½	7¼	6½	5	4*	7½	6½	5½	4½
		1600	0.75	10	8½	7½	6	4¾*	8½	7½	6½	5
		3200	0.85	11½	9½	8½	6¾	5½	10	8½	7½	5¾
KODAK T-MAX 400 Professional / TMY / 6053 KODAK T-MAX 400 Pro	120	100/200	0.52	6¾	5¾	5¼	4*	3¼*	5½	4¾	4¼	3¼*
		400	0.58	7½	6½	5¾	4½*	3½*	6¼	5¼	4¾	3¾*
		800	0.65	8½	7¼	6½	5¼	4*	7¼	6¼	5½	4¼
		1600	0.75	10	8½	7¾	6	4¾*	8½	7¼	6½	5
		3200	0.85	11½	10	9	7	5½	10	8½	7½	5¾
KODAK T-MAX P3200 Professional / TMZ / 5054	135	100/200	0.48	8½	7	6¼	5	4*	7	6	5½	4½
		400	0.52	9	7½	6¾	5½	4¼*	8	7	6	5
		800	0.58	10	8¼	7½	6	4¾*	9	8	7	5½
		1600	0.65	11	9¼	8½	7	5¼	10	9	8	6
		3200	0.75	13	11	10	8	6¼	12	10	9	7
		6400	0.85	15	12½	11½	9¼	7	14½	11½	10	8
		12500	0.95	19	15¼	13¾	10¾	8¼	17	13½	12	9
		25000	1.05	23	18½	16½	12½	9½	NR	NR	NR	NR

TABLE 1: Processing Roll Film with FRESH, FULL-STRENGTH DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	Small Tanks					Rotary Tubes (with Continuous Agitation)				
				65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	
KODAK EKTAPAN / PNT / 4162	70 mm	25/50	0.52	6	5¼	4½*	3¾*	2¾*	Not Applicable				
		100	0.58	8½	7	6¼	5	4*					
		200	0.65	10½	9	8	6½	5					
		400	0.75	13½	11½	10	8	6½					
		800	0.85	16¾	14¼	13	10	8¼					
KODAK High Speed Infrared / HIE / 2481	135	See Pub No. F-13	0.52	6½	5½	5	4*	3¼*	5¼	4½	4	3¼*	
			0.58	7¼	6	5½	4½*	3¾*	5¾	5	4½	3¾*	
			0.65	8	6¾	6	5	4¼*	6¼	5½	5	4	
			0.75	9¼	7¾	7	5¾	4¾*	7	6¼	5½	4½	
			0.85	10½	9	8	6½	5½	8	7	6¼	5¼	
AGFAPAN APX 25	135	12	0.52	4½*	3¾*	3½*	2¾*	2¼*	4	NR	NR	NR	
		25	0.58	5¾	4¾*	4¼*	3¼*	2¾*	6	4	2*	1*	
		50	0.65	8	6½	5¾	4¼*	3½*	9	6	4	2½*	
		100	0.75	14½	10¼	8¾	6½	5¼	14	10	7½	5	
		200	0.85	NR	NR	NR	NR	NR	NR	NR	NR	NR	
AGFAPAN APX 100	135	25/50	0.52	6½	5¾	5¼	4½*	3¼*	5	4½	4¼	2½*	
		100	0.58	8	6¾	6¼	5	4*	6	5½	5	3*	
		200	0.65	10	8¾	7¾	6	4¾*	7½	7	6	3¾*	
		400	0.75	13	11	10	7½	6	9½	8½	7½	4¾	
		800	0.85	15½	13	11½	9	7	12	10	9	6	
AGFAPAN 400	135	100/200	0.52	8	6½	5¾	4½*	3½*	6½	5½	4½	3½*	
		400	0.58	9½	8	7	5½	4*	8	6½	5½	4	
		800	0.65	12	9¾	8½	6½	5	9½	7¾	6½	5	
		1600	0.75	15	12¼	11	8½	6½	12	9½	8	6½	
		3200	0.85	19	14½	13½	10½	8	15	12	10	8	
FUJI NEOPAN 400 Professional	135	100/200	0.52	9	7½	6½	5	3¾*	6	5	4½	3¼*	
		400	0.58	10	8¼	7¼	5¾	4½*	7	6	5½	3¾*	
		800	0.65	11½	9¾	8¾	6½	5	8½	7¼	6½	4½	
		1600	0.75	13½	11½	10½	8	6¼	10½	9	8	5½	
		3200	0.85	16	13½	12	9½	7½	12½	11	10	7	

TABLE 1: Processing Roll Film with FRESH, FULL-STRENGTH DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	Small Tanks					Rotary Tubes (with Continuous Agitation)			
				65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)
FUJI NEOPAN 1600 Professional	135	200	0.52	4¼*	4*	3½*	3*	2¼*	3½*	3*	2¾*	2*
		400	0.58	5	4½*	4*	3¼*	2½*	4	3¼*	3*	2¼*
		800	0.65	5½	5	4½*	3½*	3*	4½	3¾*	3¼*	2½*
		1600	0.75	6½	5¾	5	4*	3½*	5¼	4½	4	2¾*
		3200	0.85	7½	6½	5½	4¾*	4*	6	5¼	4¾	3¼*
		6400	0.95	9	7¼	6½	5½	4¾*	7	6	5½	4
ILFORD PAN F Plus	135	25	0.52	7¼	6	5½	4¼*	3¼*	5	4¾	4½	2¾*
		50	0.58	8½	7	6	4¾*	3¾*	6	5½	5	3¼*
		100	0.65	9½	8	7	5½	4¼*	7	6½	6	3¾*
		200	0.75	11	9	8	6¼	4¾*	8	7½	7	4½
		400	0.85	12½	10	9	7	5½	9½	8¾	8	5¼
ILFORD FP-4 Plus	135	32/64	0.52	8	6½	5½	4½*	3½*	6	5¼	4½	3*
		125	0.58	9½	8	6½	5¼	4*	7	6	5½	3¾*
		250	0.65	11	9	7½	6	4½*	8½	7½	6½	4½
		500	0.75	14	11	9¼	7½	5½	10½	9	8	5½
		1000	0.85	17½	14	11½	9¼	7	12½	11	10	6¾
ILFORD HP-5 Plus	135	100/200	0.52	8½	7½	6¾	5¼	4*	6	5	4½	3½*
		400	0.58	10	8½	8	6¼	4¾*	7½	6¼	5½	4¼
		800	0.65	12	10½	9½	7½	5¾	9	7½	6½	5
		1600	0.75	16	13	12	9	7	11	9½	8½	6¼
		3200	0.85	NR	17½	15	11½	8½	13½	11½	10½	8
ILFORD DELTA 100 Professional	135	25/50	0.52	8	6¾	6	4½*	3½*	5½	5	4½	3½*
		100	0.58	9½	8	7	5½	4¼*	7	6	5½	4¼
		200	0.65	11½	9½	8½	6½	5	9	7½	6½	5
		400	0.75	14½	11½	10½	8	6¼	11½	9¼	8	6¼
		800	0.85	18½	14½	12¾	9½	7½	14	11½	10	7½
ILFORD DELTA 400 Professional	135	100/200	0.52	7	6	5½	4¼*	3¼*	6	5¼	4¾	3¼*
		400	0.58	8	7	6¼	5	4*	7	6¼	5½	3¾*
		800	0.65	9½	8	7½	5¾	4½*	8	7	6¼	4½
		1600	0.75	11½	10	9	7	5½	9½	8	7¼	5¼
		3200	0.85	14	12	10¾	8¼	6½	11	9¼	8½	6¼

* Development times shorter than 5 minutes (4 minutes in rotary tubes) may produce unsatisfactory uniformity.
NR= Not recommended, as determined by testing.



Important

Development times shorter than 4 minutes may produce unsatisfactory uniformity.

TABLE 2: Processing Roll Film in Replenished Systems with FULL-STRENGTH DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	Rotary Tubes (with Continuous Agitation and Seasoned Developer)				Large Tanks (with Seasoned Developer)				
				65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)
KODAK PLUS-X Pan / PX / 5062 KODAK PLUS-X 125 Pro	135	32/64	0.52	6	4 ³ / ₄	4	3*	7	5 ³ / ₄	5	3 ¹ / ₂ *	2 ¹ / ₂ *
		125	0.58	7	5¹/₂	5	3¹/₂*	7¹/₂	6¹/₂	6	4	3*
		250	0.65	8 ¹ / ₄	6 ³ / ₄	6	4	9	8	7	5	3 ³ / ₄ *
		500	0.75	10 ¹ / ₂	8 ¹ / ₂	7 ¹ / ₂	5	11 ¹ / ₂	10	9	7	5
		1000	0.85	NR	11 ¹ / ₂	10	7	16 ¹ / ₂	13	11	8 ¹ / ₂	6 ³ / ₄
KODAK PLUS-X Pan Professional / PXP / 6057 KODAK PLUS-X 125 Pro	120/220	32/64	0.52	6	4 ³ / ₄	4	3*	7 ¹ / ₂	5 ³ / ₄	5	3 ¹ / ₂ *	2 ¹ / ₂ *
		125	0.58	7	5³/₄	5	3¹/₂*	8¹/₂	6³/₄	6	4¹/₂	3¹/₄*
		250	0.65	8 ¹ / ₂	7	6	4 ¹ / ₂	10 ¹ / ₂	8 ¹ / ₂	7 ¹ / ₂	5 ¹ / ₂	4
		500	0.75	11	9	8	6	13	10 ³ / ₄	10	7 ¹ / ₄	5 ¹ / ₄
		1000	0.85	14	11 ¹ / ₂	10 ¹ / ₂	8	NR	15	13 ¹ / ₂	10	7
KODAK VERICHROME Pan / VP / 6041	120	32/64	0.52	6	5	4 ¹ / ₄	3*	7 ¹ / ₂	6 ¹ / ₄	5 ¹ / ₂	4	3*
		125	0.58	7	5³/₄	5	3¹/₂*	8¹/₂	7	6	4¹/₂	3¹/₂*
		250	0.65	8 ¹ / ₂	6 ³ / ₄	6	4 ¹ / ₂	10	8	7	5 ¹ / ₄	4
		500	0.75	11	8 ¹ / ₂	7 ¹ / ₂	5 ¹ / ₂	13 ¹ / ₂	11	9 ¹ / ₂	6 ³ / ₄	5
		1000	0.85	14	11 ¹ / ₂	10	7 ¹ / ₂	18	14	12	8 ³ / ₄	6 ¹ / ₂
KODAK TRI-X Pan / TX / 5063 KODAK TRI-X 400 Pro	135	100/200	0.52	6	5	4 ¹ / ₂	3 ¹ / ₂ *	8 ¹ / ₂	7	6 ¹ / ₄	5	3 ¹ / ₂ *
		400	0.58	7	5³/₄	5¹/₄	4	9¹/₂	8	7¹/₂	5¹/₂	4
		800	0.65	8	7	6 ¹ / ₄	5	10 ¹ / ₂	9	8	6 ¹ / ₄	4 ³ / ₄
		1600	0.75	10	8 ¹ / ₄	7 ¹ / ₂	6	12 ¹ / ₂	10 ¹ / ₂	9 ¹ / ₂	7 ¹ / ₂	5 ¹ / ₂
		3200	0.85	12	10	9	7	14 ¹ / ₂	12	11	8 ¹ / ₂	6 ¹ / ₂
KODAK TRI-X Pan / TX / 6043 KODAK TRI-X 400 Pro	120	100/200	0.52	6	5	4 ¹ / ₂	3 ¹ / ₄ *	8	6 ¹ / ₂	5 ¹ / ₂	4	3*
		400	0.58	7	6	5¹/₄	4	9	7¹/₂	6¹/₂	4³/₄	3³/₄*
		800	0.65	8	6 ³ / ₄	6	4 ³ / ₄	10 ¹ / ₂	8 ³ / ₄	7 ³ / ₄	5 ³ / ₄	4 ¹ / ₂ *
		1600	0.75	10	8 ¹ / ₂	7 ¹ / ₂	5 ¹ / ₂	12 ¹ / ₂	10 ¹ / ₂	9 ¹ / ₂	7	5 ¹ / ₄
		3200	0.85	12	10	9	6 ¹ / ₂	14 ¹ / ₂	12 ¹ / ₂	11	8 ¹ / ₄	6 ¹ / ₄

TABLE 2: Processing Roll Film in Replenished Systems with FULL-STRENGTH DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	Rotary Tubes (with Continuous Agitation and Seasoned Developer)				Large Tanks (with Seasoned Developer)				
				65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)
KODAK TRI-X Pan Professional / TXP / 6049	120/220	100/200	0.52	6	5	4¼	3½*	7½	6¼	5½	4¼	3½*
		400	0.58	7	5¾	5	4¼	9½	7½	6½	5¼	4¼
		800	0.65	8	6¾	6¼	5	11½	9¼	8	6¼	5
		1600	0.75	11	9¼	8	6½	15	11¾	10	8	6½
		3200	0.85	NR	11½	10	8	18½	15	13	10½	7¾
KODAK T-MAX 100 Professional / TMX / 5052 KODAK T-MAX 100 Pro	135	25/50	0.52	7½	6½	6	4	9½	8	7¼	5½	4¼
		100	0.58	9	7¾	7	5	11½	9½	8½	6¼	5
		200	0.65	11	9	8	6	13½	11¼	9¾	7½	5¾
		400	0.75	13½	11	9½	7	15½	13	11½	8¾	6¾
		800	0.85	17½	13½	11	8	18	15¼	13½	10	7½
KODAK T-MAX 100 Professional / TMX / 6052 KODAK T-MAX 100 Pro	120	25/50	0.52	8	6	5	3¾*	9	7½	6½	5	3¾*
		100	0.58	9½	7	6	4½	11	8¼	7½	5½	4¼
		200	0.65	11	8¼	7	5¼	11¼	9½	8½	6¼	5
		400	0.75	13	10	8½	6¼	12½	10¾	10	7¼	5¾
		800	0.85	15½	12	10	7½	15	12½	11½	8½	6¾
KODAK T-MAX 400 Professional / TMY / 5053 KODAK T-MAX 400 Pro	135	100/200	0.52	7	6	5½	4	8	6¾	6	5	3½*
		400	0.58	8	6¾	6	4½	9	7¾	7	5½	4
		800	0.65	9	7¾	7	5	10½	9	8	6	4½
		1600	0.75	10½	9	8	6	12	10	9	7	5¼
		3200	0.85	12	10¼	9	7	13½	11½	10	8	6
KODAK T-MAX 400 Professional / TMY / 6053 KODAK T-MAX 400 Pro	120	100/200	0.52	7¼	5½	4½	3¾*	8½	7¼	6	4¾	3½*
		400	0.58	8¼	6½	5½	4¼	9¼	7¾	6¾	5¼	4
		800	0.65	9½	7½	6¼	4¾	10	8½	7½	6	4½
		1600	0.75	11	8¾	7½	5¾	11¾	10	8¾	6¾	5¼
		3200	0.85	12½	10	8½	6¾	13¼	11¼	10	7¾	6
KODAK T-MAX P3200 Professional / TMZ / 5054	135	100/200	0.48	9	7	6	5	10	8	7½	5½	4½
		400	0.52	10	8	7	5½	11	9	8	6¼	5
		800	0.58	11	9¼	8	6	12	10	9	7	5½
		1600	0.65	13	10¼	9	7	13	11	10	7¾	6
		3200	0.75	15	12	10½	8	15	13	11½	9	7
		6400	0.85	17	13½	12	9	16½	15	13½	10½	8
		12500	0.95	20	15½	13½	10½	21	17	15½	12½	9½
		25000	1.05	24	18	16	13	NR	21	18½	15	11½

TABLE 2: Processing Roll Film in Replenished Systems with FULL-STRENGTH DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	Rotary Tubes (with Continuous Agitation and Seasoned Developer)				Large Tanks (with Seasoned Developer)				
				65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)
KODAK High Speed Infrared / HIE / 2481	135	See Pub No. F-13	0.52	6½	5¾	5¼	4	8½	6¾	6	4¾	4
			0.58	7¼	6¼	5¾	4½	10	8	7	5½	4½
			0.65	8	7	6½	5	11½	9	8	6¼	5
			0.75	9½	8¼	7½	6	13	10¼	9	7	5½
			0.85	11	9¼	8½	7	14½	11½	10	7¾	6
AGFAPAN APX 25	135	12	0.52	4	3*	NR	NR	6½	5¼	4½	3½*	3*
		25	0.58	6	5	4½	3*	8½	6½	5¾	4½	4
		50	0.65	10	7½	6½	4½	12½	10	8½	6½	5
		100	0.75	15	12	10½	7½	NR	16	14	11	8
		200	0.85	NR	NR	NR	NR	NR	NR	NR	NR	NR
AGFAPAN APX 100	135	25/50	0.52	7	6	5½	3½*	9	7	6½	5	4
		100	0.58	8½	7¼	6½	4¼	11	9	8	6½	5
		200	0.65	10½	9	8	5¼	13½	11	10	8	6
		400	0.75	13	11	10	6½	17½	14	12	9½	7½
		800	0.85	17	14½	13	8	NR	19	16	12	9½
AGFAPAN 400	135	100/200	0.52	8	6½	5½	4¼	10	8	7½	5½	4
		400	0.58	9½	7½	6½	5	12	10	9	6½	5
		800	0.65	12	9½	8	6	14	11½	10½	8	6
		1600	0.75	15	12½	10½	7½	18½	14	12½	9½	7½
		3200	0.85	18	15	13	9½	NR	20	16½	11½	9
FUJI NEOPAN 400 Professional	135	100/200	0.52	7	6	5¼	3½*	9	7½	6¾	5	4
		400	0.58	8	7	6¼	4¼	10	8¼	7½	5½	4½
		800	0.65	9½	8	7¼	5	11½	9½	8½	6½	5
		1600	0.75	11½	9¾	8½	6	13½	11½	10	8	6
		3200	0.85	13½	11½	10	7½	16	13½	12	9½	7
FUJI NEOPAN 1600 Professional	135	200	0.52	4¼	3½*	3¼*	2½*	5½	4¾	4¼	3¼*	2½*
		400	0.58	4¾	4	3½*	2¾*	6	5¼	4¾	3¾*	3*
		800	0.65	5½	4¾	4	3*	6¾	6	5½	4¼	3½*
		1600	0.75	6½	5½	4¾	3¼*	8	7	6¼	5	4
		3200	0.85	7½	6¼	5½	4	9	8	7	5½	4½
		6400	0.95	8½	7½	6½	4¾	10½	9	8	6¼	5

TABLE 2: Processing Roll Film in Replenished Systems with FULL-STRENGTH DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	Rotary Tubes (with Continuous Agitation and Seasoned Developer)				Large Tanks (with Seasoned Developer)				
				65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)
ILFORD PAN F Plus	135	25	0.52	7	6¼	5½	3¼*	9½	7½	7	5	3½*
		50	0.58	8½	7¼	6½	4	11	9	8	6	4½
		100	0.65	10	8½	7½	5	13	11	9½	7	5
		200	0.75	12	10¼	9½	6	16	13	11½	8½	6
		400	0.85	14½	12½	11	7	19	16	14	10½	7½
ILFORD FP-4 Plus	135	32/64	0.52	9½	7¾	6½	4½	11½	9	8	6	4½
		125	0.58	11	9	7½	5¼	13½	11	9½	7	5
		250	0.65	13	10¾	9½	6¼	16	12½	11	8	6
		500	0.75	16	13½	12	7¾	21	15½	13½	10	7
		1000	0.85	19	16	14	9½	NR	NR	17	12½	9
ILFORD HP-5 Plus	135	100/200	0.52	8½	6¾	5½	4	11½	9	8	6	4½
		400	0.58	9½	7¾	6½	5	13¼	10½	9½	7	5½
		800	0.65	11½	9½	8	6	15¾	13	11½	8½	6½
		1600	0.75	14	11½	10	7¼	NR	15½	13½	10	8
		3200	0.85	17	14¼	12½	9	NR	19½	17½	13	10
ILFORD DELTA 100 Professional	135	25/50	0.52	8½	7¼	6½	4¼	10½	8	7	5½	4¼
		100	0.58	10½	8½	7½	5¼	12½	10	8½	6½	5
		200	0.65	13	10½	9	6½	15½	12	10½	8	6
		400	0.75	16½	13½	11½	8	NR	15	13	10	7½
		800	0.85	20	16½	14½	10	NR	19	16½	12½	9½
ILFORD DELTA 400 Professional	135	100/200	0.52	7½	6¼	5½	4	9	7½	6½	5	4
		400	0.58	8½	7	6¼	4½	10½	8½	8	6	4½
		800	0.65	10	8¼	7¼	5¼	12	10	9	7	5¼
		1600	0.75	12	9½	8½	6¼	14	11½	10	8	6
		3200	0.85	14½	11½	10	7½	16½	13½	12	9½	7½

* Development times shorter than 4 minutes may produce unsatisfactory uniformity.
NR= Not recommended, as determined by testing.



Important

Development times shorter than 5 minutes (4 minutes in rotary tubes) may produce unsatisfactory uniformity.

TABLE 3: Processing Roll Film with FRESH, DILUTE DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	In Small-Tanks, DEVELOPER DILUTION												In Rotary-Tubes (with Continuous Agitation), DEVELOPER DILUTION											
				1:1				1:2				1:3				1:1				1:2				1:3			
				68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)
KODAK PLUS-X Pan / PX / 5062 KODAK PLUS-X 125 Pro	135	32/64	0.52	6½	6	5	4*	7½	7	5½	4½*	9½	8½	6½	5¼	4½	4	3*	2¼*	5½	5	3½*	2¾*	6	5½	4¼	3¼*
		125	0.58	7½	7	5½	4½*	8½	8	6½	5¼	10½	9½	7½	6	5¾	5	3¾*	2¾*	6½	5¾	4¼	3¼*	7	6½	5	4
		250	0.65	8¾	8	6½	5¼	9¾	9	7½	6	12	11	9	6¾	6¾	6	4½	3¼*	7½	6½	5	4	8¼	7½	6	5
		500	0.75	11	10	8	6½	13	12	9½	7½	15½	14	11½	8	8	7	5½	4	9	8	6¼	5	10	9	7½	6
		1000	0.85	15½	14	11	8½	16½	15	12½	9	19½	18	15	10	9½	8½	6½	5	11	10	8	6	12	11	9	7½
KODAK PLUS-X Pan Professional / PXP / 6057 KODAK PLUS-X 125 Pro	120/ 220	32/64	0.52	6	5½	4¼*	3*	7¼	6¾	5	3¼*	8¾	8¼	6½	4½*	4½	4	2¾*	2*	5½	5	4	2¾*	6¾	6	4½	3½*
		125	0.58	7¼	6½	5	3½*	8½	8	6¼	4¼*	10¼	9½	7½	5½	5¾	5	3½*	2½*	6¾	6	4½	3¼*	7¾	7	5¼	4
		250	0.65	8¾	8	6	4¼*	10¼	9½	7½	5¼	12	11¼	9	6½	6¾	6	4¼	3¼*	7¾	7	5¼	4	8¾	8	6¼	5
		500	0.75	11	10	7¾	5½	12¾	12	9¾	6¾	14½	13½	11	8	8¾	7½	5¼	4	9¼	8½	6½	5	10¼	9½	7¾	6¼
		1000	0.85	15¼	14	11	7	16¾	16	13	9	18¼	17	13¾	10	11½	10	7	5¼	12	11	8	6¼	13¼	12	9¾	8
KODAK VERICHROME Pan / VP / 6041	120	32/64	0.52	6¾	6	4½*	2¾*	7½	7	5¼	3½*	9¼	8½	6½	4½*	4½	4	3*	2¼*	5¾	5	3¾*	3*	6¾	6	4½	3½*
		125	0.58	7½	7	5¼	3¼*	8½	8	6¼	4½*	10¼	9½	7½	5½	5¾	5	3¾*	2¾*	6¾	6	4½	3½*	7¾	7	5¼	4¼
		250	0.65	8¾	8	6¼	4¼*	10¼	9½	7½	5½	11¾	11	9	6½	6¾	6	4½	3¼*	8	7	5½	4¼	8¾	8	6¼	5
		500	0.75	10¾	10	8	5½	12¾	12	9¾	7	14	13¼	11	8	8½	7½	5½	4¼	9¼	8½	6¾	5	10¼	9½	7¾	6
		1000	0.85	13¾	13	10½	7½	16¾	15	12	8½	16½	15½	13¼	10	11	9½	6¾	5¼	11¼	10½	8¼	6	13	12	9½	7¼
KODAK TRI-X Pan / TX / 5063 KODAK TRI-X 400 Pro	135	100/200	0.52	8	7½	6½	5½	8¾	8½	7½	6½	10¾	10	8½	7½	5½	5	3¾*	3*	6½	6	4½	3½*	7½	7	5¾	4½
		400	0.58	8¾	8¼	7	6	10½	10	8½	7	12½	11½	9½	8¼	6¾	6	4½	3½*	7½	7	5½	4	9	8	6½	5
		800	0.65	10	9½	8	6½	12½	11½	9½	7½	14	13	11	9	7¾	7	5¼	4	8¾	8	6½	5	10½	9½	7¾	6
		1600	0.75	11¾	11	9	7¼	14½	13½	11	8½	16½	15½	12¾	10¼	9	8	6¼	4¾	10½	9½	8	6	12	11	9	7
		3200	0.85	13½	12½	10½	8	17	15½	12½	9½	20	18	15	11½	10½	9½	7¼	6	12½	11½	9½	7	14	13	10½	8½
KODAK TRI-X Pan / TX / 6043 KODAK TRI-X 400 Pro	120	100/200	0.52	6¾	6¼	5	3¾*	8½	8	6¼	4½*	9½	8¾	7	5½	5	4½	3½*	3*	6¼	6	5	3½*	8¼	7½	5¾	4¼
		400	0.58	8	7¼	6	4½*	10¼	9½	7½	5½	11	10½	8½	6½	6¼	5½	4¼	3½*	7¼	7	5¾	4	9¼	8½	6¾	5
		800	0.65	9¼	8½	7	5½	12	11	9	6½	13½	12½	10	7½	7¼	6½	5	4	8½	8	6¾	4¾	11	10	7¾	5¾
		1600	0.75	11	10½	8½	6½	14½	13½	10¾	7¾	16¼	15¼	12½	9	9	8	6	4¾	10½	10	8¼	5¾	13	12	9¼	7
		3200	0.85	13½	12½	10¼	7¾	17	16	13	9½	19¾	18½	15	11	11½	10	7¼	5¾	12¾	12	9¾	6¾	15¼	14	10¾	8¼

TABLE 3:

Processing Roll Film with FRESH, DILUTE DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	In Small-Tanks, DEVELOPER DILUTION												In Rotary-Tubes (with Continuous Agitation), DEVELOPER DILUTION											
				1:1				1:2				1:3				1:1				1:2				1:3			
				68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)
KODAK TRI-X Pan Professional / TXP / 6049	120/220	80/160	0.52	7¾	7	5½	4*	10¼	9½	7½	6	12¼	11½	9½	7½	5¾	5¼	4	3¼*	6¾	6½	5¾	4¼	9	8½	7	5¼
		320	0.58	8¾	8	6½	5	12	11	9	7	14¼	13¼	11	9	6¾	6	4¾	3¾*	7¾	7½	6¾	5	10½	10	8	6¼
		640	0.65	10¼	9½	8	6	14	13	10½	8½	17¼	16¼	13½	10½	7¾	7	5½	4½	9¼	9	8	5¾	12¼	11½	9¼	7¼
		1250	0.75	12¾	12	10	8	16½	15¼	13	10	21½	20	16½	13	9¼	8½	6¾	5½	11½	11	9½	7	15	14	11	9
2500	0.85	15¾	14½	12	10	21	19½	16	12½	25½	24	20	16½	11½	10½	8¼	6½	14	13½	11¼	8½	18½	17	13¾	11		
KODAK T-MAX 100 Professional / TMX / 5052 KODAK T-MAX 100 Pro	135	25/50	0.52	8	7¼	6	5	11½	10½	8½	6½	14½	13½	11½	9	7¾	7	5½	4½	10½	9½	7½	6	14	13	10	8
		100	0.58	9¼	8½	7	5½	12½	11½	9½	7¼	16	15	12½	10	8¾	8	6¼	5	12	11	8½	7	15½	14½	11½	9
		200	0.65	10¼	9½	8	6¼	13¾	13	10½	8¼	18¼	17	14	11	9¾	9	7¼	6	13½	12½	10	8	18	16½	13	10
		400	0.75	12¼	11½	9	7	15¾	14½	12	9½	20½	19	15½	12½	11½	10½	8½	7	15½	14	11½	9	21	19½	15	11½
800	0.85	14½	13	10½	8	18	16½	13½	10½	23	21	17½	14	13	12	9¾	8	18	17	13½	10	NR	23	17½	13		
KODAK T-MAX 100 Professional / TMX / 6052 KODAK T-MAX 100 Pro	120	25/50	0.52	8¾	8	6	4½*	11¾	11	8¾	7	15	14	11¼	9½	6¾	6½	6	5½	8¾	8½	7¾	7	11½	11	10	9½
		100	0.58	10	9	6¾	5¼	13	12	10	8	16¾	15½	12¾	10½	7¾	7½	6¾	6	10	9½	8½	8	13	12½	11½	10½
		200	0.65	11	10	7½	6	14½	13½	11¼	9	18¾	17½	14¼	11½	8¾	8½	7¾	7	11½	11	10	9	15¼	14½	12¾	11½
		400	0.75	12¾	11½	8¾	6¾	16¾	15½	12½	10	21	19½	16	12½	10¼	9¾	8¾	8	13½	13	11½	10	18½	17½	15	12½
800	0.85	15¼	13½	10	7½	19	17½	13¾	11	23½	22	18¼	14	11½	11	10	9	15¾	15	13	11	23½	22	18	14		
KODAK T-MAX 400 Professional / TMY / 5053 KODAK T-MAX 400 Pro	135	100/200	0.52	8	7½	6½	5½	9½	9	7½	6½	12¼	11½	10	8	6½	6	4¾	4	8½	8	6½	5	10½	10	8	6½
		400	0.58	8¾	8	7	6	10½	10	8½	7	13½	13	11	8¾	7¾	7	5½	4½	9½	9	7½	5¾	12	11½	9¼	7½
		800	0.65	9½	9	7¾	6½	12¼	11½	9½	7½	15	14	12½	9½	8¾	8	6¼	5	10¾	10	8½	6½	14	13	10½	8½
		1600	0.75	10¾	10	8½	7	13¾	13	11	8½	17	16	14	11	10	9¼	7¼	6	12½	11½	10	7½	16¼	15	12	9½
3200	0.85	12½	11½	9¼	7½	16	15	12½	9½	20	18½	16	12	11½	10½	8½	7	14½	13½	11½	8½	18	17	13¾	10½		
KODAK T-MAX 400 Professional / TMY / 6053 KODAK T-MAX 400 Pro	120	100/200	0.52	8	7½	6¼	5	11	10	8	6½	13¾	12½	9½	8	6	5½	4½	3¾*	8	7½	6½	5	10½	10	8	6½
		400	0.58	9¼	8½	7	5½	12½	11½	9	7¼	15½	14	11	9	7	6½	5¼	4¼	9	8½	7¼	5½	11¾	11	9	7
		800	0.65	10¾	10	8	6	14¼	13	10¼	8	17¼	15½	12½	10	8¼	7½	6	4¾	10½	9½	8	6	13	12	10	7¾
		1600	0.75	12½	11½	9¼	7	16½	15	11¾	9¼	19½	18	14	11½	9¾	9	7	5½	12	11	9	7	15	14	11½	8¾
3200	0.85	14¼	13	10½	8	19¼	17½	13½	10½	22¾	20½	16	13	11¼	10½	8¼	6¼	14	13	10½	8	17¼	16	13	10		
KODAK T-MAX P3200 Professional / TMZ / 5054	135	100/200	0.48	10½	9½	7½	6½	14¼	13	10	8	17¼	16	12½	10½	9¼	8½	6¾	5½	12	11	8½	7	15½	14	10½	8½
		400	0.52	11½	10	8½	7	15½	14	11	8½	18½	17	14	11½	9¾	9	7¼	6	13	12	9½	7½	16½	15	11½	9
		800	0.58	12½	11½	9	7½	16½	15	12	9½	20½	19	15½	12½	10¾	10	8	6½	14¼	13	10½	8¼	18	16½	13	10
		1600	0.65	14	13	10	8	19	17	13½	10½	23	21½	17	14	12	11	9	7	15½	14½	11½	9	19½	18	14½	11
		3200	0.75	16½	15	11½	9	22	20	15½	12½	27	24	20	16	13½	12½	10	8	17½	16	13	10½	22	20½	16½	12½
		6400	0.85	19½	17½	14	10½	26½	23	18½	14½	NR	28	24	18½	15½	14½	11¾	9½	19½	18	14½	12	25½	23½	18½	14
		12500	0.95	22½	20	16½	12½	NR	26	22	17	NR	NR	28	21	17½	16½	13½	11	22	20	16½	13½	28½	26	20½	16
25000	1.05	26	22½	20	15	NR	NR	NR	20	NR	NR	NR	23½	21	19½	16	13	25	23	18½	15	NR	NR	23	18		

TABLE 3: Processing Roll Film with FRESH, DILUTE DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	In Small-Tanks, DEVELOPER DILUTION												In Rotary-Tubes (with Continuous Agitation), DEVELOPER DILUTION											
				1:1				1:2				1:3				1:1				1:2				1:3			
				68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)
KODAK High Speed Infrared / HIE / 2481	135	See Pub No. F-13	0.52	8	7½	6¼	5	11½	10½	8½	7	15¼	14	11¼	9	6½	6	5	4	9¼	8½	7	5½	12	11	9	7
			0.58	8¾	8¼	7	5½	12½	11½	9	7½	17	15½	12¼	10	7	6½	5½	4½	10	9	7½	6	13½	12½	10	8
			0.65	9¾	9	7½	6	13¾	12¾	10	8¼	18½	17	13¾	11	8	7¼	6	5	11	10	8	6½	15	13½	11	9
			0.75	10¾	10	8½	6¾	15¾	14½	11½	9	21	19¼	15½	12½	9	8½	7	5½	12½	11½	9¼	7¼	17	15½	12½	10
			0.85	12½	11½	9¼	7½	18	16½	13	10½	24	22	17½	14½	10	9½	8	6½	14½	13	10½	8½	19	17½	14	11½
AGFAPAN APX 25	135	12	0.52	5	4½*	3½*	2¾*	7¾	7	5½	4*	10¼	9½	7¾	6	4	3½*	2½*	1¾*	5½	5	4¼	3*	7	6½	5½	4
		25	0.58	6	5½	4½*	3½*	9¼	8½	6¾	5	11¾	11	9	7	4½	4	3*	2*	6¼	5¾	4¾	3½*	8	7½	6	4½
		50	0.65	8	7½	6	4½*	11	10	8	6	14	13	10½	8½	5½	5	3¾*	2¾*	7	6½	5½	4	9	8½	7	5¼
		100	0.75	10½	9½	7¾	6	14	13	10½	8	17½	16	13	10	7¼	6½	5	3½*	9	8½	6¾	5	11¼	10¼	8½	6¼
		200	0.85	14½	13	10½	8½	17	16	13	10½	21½	20	16	13	9¼	8½	6½	5	12¼	11½	9	6½	13½	13	10½	8
AGFAPAN APX 100	135	25/50	0.52	8	7½	6	4¾*	12	11	8½	7	15¼	14	11½	10	5¾	5¼	4¼	3*	8	7½	6½	5	11¾	11	9	7
		100	0.58	9¾	9	7	5½	13¾	12½	9¾	8	17¼	16	13	11½	6½	6	5	3¾*	9¼	8¾	7½	5¾	12¾	12	10¼	8
		200	0.65	12	11	8¼	6½	15¼	14	11	9	19½	18	15	13	7½	7	5¾	4½	11¼	10½	8½	6½	14¼	13½	11½	9½
		400	0.75	15½	13½	10	7½	18¾	17	13	10½	23	21	17¾	15	9¼	8½	7	5½	14	13	10½	7½	17	16	13½	11
		800	0.85	22	18½	13	9	23	20½	16	12½	29	25	21	17	12	11	9	7	17	16	12½	9	19¾	19	16	13½
AGFAPAN 400	135	100/200	0.52	10½	9	6½	5	13½	12	8½	6½	16½	15	11½	8½	7¼	6½	5	4	9¼	8½	7	5	11¼	10½	8	6½
		400	0.58	12	10½	8	6	15¾	14	10½	8	19¼	17½	13½	10½	8¾	8	6¼	5	11½	10½	8½	6	13¼	12½	9½	7½
		800	0.65	14½	13	9½	7½	19	17	12½	9½	22½	20½	16	12½	11	10	7¾	6	13½	12½	10	7	16	15	11½	9
		1600	0.75	18	16½	12½	9½	23	21	16	12	28½	26	20	15½	14¼	13	9¾	7	16½	15½	12½	9	20	18½	14	11
		3200	0.85	21	20	16	12	NR	25	19	15	NR	NR	25	20	19	17	12¾	9	20	18½	15	11	NR	22½	17	14
FUJI NEOPAN 400 Professional	135	100/200	0.52	8¼	7½	6	4½*	11	10	7¾	6½	13½	12½	10	8	6½	5½	4	3½*	8½	8	6¼	5¼	12	11	8½	7
		400	0.58	9¾	9	7	5¼	12½	11½	9	7½	15¾	14½	11½	9	7½	6½	4¾	4	9¾	9	7¼	5¾	13½	12½	9¾	7¾
		800	0.65	11½	10½	8	6	14½	13	10½	8½	18½	16½	13	10	9	8	5¾	4¾	11½	10½	8¼	6½	15¼	14	11	8½
		1600	0.75	13½	12½	9¾	7¼	17	15½	12	9½	22½	20	15½	11½	11	10	7¼	5¾	13½	12½	9½	7½	18	16½	13	9½
		3200	0.85	16½	15	11½	8½	20½	18½	14	11	26	23½	18	13½	13	12	9	6¾	15¾	14½	11½	8¾	21	19½	15½	11
FUJI NEOPAN 1600 Professional	135	200	0.52	5½	5	4*	3½*	7	6½	5¼	4½*	9¼	8½	7	5½	4½	3¾*	3*	2½*	5¼	5	4¼	3½*	7	6½	5¼	4¼
		400	0.58	6	5½	4½*	3¾*	7¾	7¼	5¾	4¾*	10¼	9½	7½	6	5	4¼	3¼*	2¾*	5¾	5½	4½	3¾*	7¾	7¼	5¾	4¾
		800	0.65	6¾	6¼	5	4¼*	8½	8	6½	5¼	11½	10½	8¼	6¾	5½	4¾	3¾*	3*	6½	6	5	4	8½	8	6¼	5¼
		1600	0.75	7½	7	5¾	4¾*	10	9¼	7½	6	13	12	9½	7½	6¼	5½	4¼	3½*	7¼	6¾	5½	4½	9½	9	7¼	5¾
		3200	0.85	8½	8	6½	5¼	11¼	10½	8½	6¾	14¾	13½	10½	8½	7	6¼	5	4	8¼	7¾	6½	5¼	10¾	10	8¼	6½
		6400	0.95	9¾	9	7½	6	13	12	9¾	7½	16½	15	12	9½	7¾	7	5¾	4½	9½	9	7½	6	12¼	11½	9½	7½

TABLE 3: Processing Roll Film with FRESH, DILUTE DEVELOPER (Development Times in minutes)

ROLL FILM	FORMAT	EI	CI	In Small-Tanks, DEVELOPER DILUTION												In Rotary-Tubes (with Continuous Agitation), DEVELOPER DILUTION											
				1:1				1:2				1:3				1:1				1:2				1:3			
				68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)
ILFORD PAN F Plus	135	25	0.52	6¾	6	4½*	3½*	8¾	8	6	4½*	10½	9½	7½	5½	5	4½	3½*	3*	6½	6	4¾	3¾*	8¼	7½	5½	4½
		50	0.58	7¾	7	5¼	4*	10	9	7	5	12	11	8½	6¼	5¾	5¼	4	3¼*	7¼	6¾	5¼	4¼	9½	8½	6¼	5
		100	0.65	9½	8½	6¼	4½*	11½	10½	8	5¾	13½	12½	9¾	7¼	6½	6	4¾	3¾*	8¼	7½	6	4¾	10½	9½	7	5½
		200	0.75	11¼	10	7½	5½	13¼	12	9	6¾	15¾	14½	11¼	8½	7½	7	5½	4¼	9½	8¾	7	5¼	11¾	10½	8	6¼
		400	0.85	13	11½	8½	6½	15½	14	10½	8	18½	16¾	13	10	8½	8	6¼	4¾	11½	10½	8	5¾	13½	12	9	7
ILFORD FP-4 Plus	135	32/64	0.52	8½	7½	5½	4*	10	9	7	5	12½	11	8	6½	6¼	5½	4	3*	7¼	6½	5	3½*	9	8	6	4¼
		125	0.58	10	9	6½	5	11½	10½	8	6	14¾	13	9½	7½	7¼	6½	4¾	3½*	8¼	7½	5¾	4	10	9	6¾	5
		250	0.65	12	10¾	8	6	13¾	12½	9½	7	17	15	11	9	8¼	7½	5½	4	9½	9	6¾	4¾	11½	10½	7¾	5¾
		500	0.75	14½	13	9½	7	17¼	15½	11½	8	20	18	13½	10½	9¾	9	6¾	5	11¼	10½	8	5¾	14¼	13	9¾	6¾
		1000	0.85	17½	15½	11½	8½	21	18½	13½	9½	23½	21	16	12½	11¼	10½	8	6	13¾	12½	9½	7	18¼	16½	12	8
ILFORD HP-5 Plus	135	100/200	0.52	10¼	9	6½	5	12¾	11½	8½	6½	14½	13	10	8	7½	6½	4½	3½*	8½	8	6¼	4¼	10½	9½	7	5¼
		400	0.58	12	10½	7½	5¾	15½	14	10½	7½	18	16	12	9½	9	8	5½	4¼	9½	9	7¼	5¼	12¼	11	8½	6¼
		800	0.65	14¼	12½	8¾	6½	18	16½	12½	9	23	20	15	11	10½	9½	7	5¼	11¾	11	9	6½	14¼	13	10	7½
		1600	0.75	18	16	11½	8	21	19	15	11	27½	25	18¾	13½	12½	11½	9	6½	14½	13½	11	8	17½	16	12½	9½
		3200	0.85	22½	20	14	10	NR	22½	17¾	13½	NR	NR	NR	16½	15	14	11	8¼	17½	16½	13½	10	21½	19½	15	11½
ILFORD DELTA 100 Professional	135	25/50	0.52	9	8	6	4¾*	11	10	8	6	13½	12	9½	7½	6¾	6	4¼	3½*	8¼	7½	5¾	4¼	9¾	9	7	5¼
		100	0.58	10½	9½	7¼	5½	13	12	9	7	15½	14	11	9	7¾	7	5	4	10	9	6¾	5	11¾	10½	8	6¼
		200	0.65	12	11	8½	6½	15	14	10½	8	17½	16½	12¾	10½	8¾	8	6	5	11½	10½	8	6	13¼	12	9½	7¼
		400	0.75	14	12¾	10¼	8	17½	16	12½	9½	20½	19½	15	12½	11	10	7½	6	13¾	12½	9½	7¼	15¾	14½	11½	8½
		800	0.85	16¾	15½	12½	9½	21½	19½	14½	11½	24¼	22½	18	14½	13½	12	9	7	17	15	11	8½	19¼	17½	13½	10
ILFORD DELTA 400 Professional	135	100/200	0.52	9	8	6	4¾*	12	10½	7½	5½	14½	13	10	7¾	7	6	4½	3¼*	8¼	7½	5¾	4¼	10½	9½	7	5¼
		400	0.58	10½	9½	7	5½	14	12½	9	6½	16½	15	11½	9	8	7	5¼	4	10	9	6¾	5	12¼	11	8¼	6¼
		800	0.65	12¼	11	8½	6½	16¼	14½	10½	7¾	19½	17½	13½	10½	9	8	6	5	11½	10½	8¼	6	14¼	13	10	7¾
		1600	0.75	14½	13	10	8	19½	17½	13	9½	23	21	16½	13	11	10	7½	6	14¼	13	10¼	7½	17½	16	12½	9½
		3200	0.85	17	15½	12	9½	23½	21½	16	11½	NR	26	20	15½	13½	12½	9½	7½	18	16½	13	9½	22½	20	15	12

* Development times shorter than 5 minutes (4 minutes in rotary tubes) may produce unsatisfactory uniformity.
NR= Not recommended, as determined by testing.

TABLE 4: Processing KODAK Technical Pan Film / 2415 in Small Tanks
with FRESH, DILUTE DEVELOPER and Normal Agitation (Development Time in minutes)

ROLL FILM	FORMAT	EI	CI	DEVELOPER DILUTION			
				1:2	1:3	1:4	1:5
				70°F (21°C)	70°F (21°C)	70°F (21°C)	70°F (21°C)
KODAK Technical Pan / 2415	135	4	0.60	6			
		6	0.60		9		
		8	0.60			12	
		10	0.60				15* 16†

* Using 16 fluidounces of developer per roll
† Using 8 fluidounces of developer per roll

Sheet Films

**Important**

Development times shorter than 4 minutes may produce unsatisfactory uniformity.

**TABLE 5: Processing Sheet Film in Trays or Large Tanks with FULL-STRENGTH DEVELOPER
(Development Times in minutes)**

SHEET FILM	EI	CI	Fresh Developer in Trays					Seasoned Developer in Large Tanks				
			65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)
KODAK PLUS-X Pan Professional / PXT / 4147	32/64	0.52	6½	5¼	4¾	3¾*	3*	7½	6½	5½	4	3¼*
	125	0.58	7½	6¼	5¾	4½	3½*	8½	7¼	6½	4¾	3¾*
	250	0.65	9¼	7¾	7	5½	4½	10½	8¾	7¾	6	4½
	500	0.75	12	10	9	7	5½	14¼	12	10½	8½	6½
	1000	0.85	15	12¾	11½	9	7¼	18	15	13½	10½	8½
KODAK T-MAX 100 Professional / TMX / 4052	25/50	0.52	7½	6¼	5½	4½	3½*	9½	8	6¾	5½	4
	100	0.58	8½	7¼	6½	5	4	10¾	9	8	6¼	4¾
	200	0.65	9½	8¼	7½	5½	4½	12	10¼	9	7¼	5½
	400	0.75	10¾	9½	8½	6½	5¼	14½	12	11	8½	6½
	800	0.85	12	11	10	7½	6	16½	14	12½	9¾	7½
KODAK TRI-X Pan Professional / TXT / 4164	80/160	0.52	6¼	5¼	4¼	3¾*	2¾*	7	6	5	4	2¾*
	320	0.58	7½	6½	5¾	4½	3½*	8½	7	6	4¾	3½*
	640	0.65	9¼	7¾	7	5¼	4¼	10½	8¾	7½	6	4½
	1250	0.75	11½	9½	8½	6½	5¼	12¾	10¾	9½	7½	5¾
	2500	0.85	14	11¾	10½	8	6¾	15½	13¼	12	9¼	7¼
KODAK T-MAX 400 Professional / TMY / 4053	100/200	0.52	7½	6½	5½	4½	3½*	9¼	7¾	6½	5¼	4
	400	0.58	8½	7¼	6¼	5	4	10	8½	7¼	5¾	4½
	800	0.65	9¼	8	7	5½	4½	11¼	9½	8¼	6½	5
	1600	0.75	10¾	9¼	8	6½	5	13	11	9¾	7¾	6
	3200	0.85	12½	10½	9	7½	5¾	14¾	12½	11	8¾	6¾
KODAK EKTAPAN / PNT / 4162	25/50	0.52	6¾	5½	4¾	3¾*	2¾*	7½	6¼	5¼	4¼	3*
	100	0.58	8½	7¼	6¼	5	3¾*	9½	8	6¾	5½	4
	200	0.65	10½	9	7¾	6	4¾	12	10	9	7	5¼
	400	0.75	13½	11½	10	8	6¼	16	13½	12	9½	7½
	800	0.85	17½	15	13	10	8	NR	17½	15	12	9½

* Development times shorter than 4 minutes may produce unsatisfactory uniformity.
NR= Not recommended, as determined by testing.



Important

Development times shorter than 4 minutes may produce unsatisfactory uniformity.

**TABLE 6: Processing Sheet Film in Rotary Tubes with FULL-STRENGTH DEVELOPER
(Development Times in minutes)**

SHEET FILM	EI	CI	Fresh Developer				Replenished Developer			
			65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	65°F (18°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)
KODAK PLUS-X Pan Professional / PXT / 4147	32/64	0.52	4½	3¾*	3¼*	2¾*	5½	4½	4	3*
	125	0.58	5½	4½	4	3*	7	5¾	5	3¾*
	250	0.65	7	5¾	5	4	9	7¼	6	4¾
	500	0.75	9½	8	7	5¼	12½	9¾	8	6
	1000	0.85	13	11¼	10	7½	17	13¾	11½	9
KODAK T-MAX 100 Professional / TMX / 4052	25/50	0.52	6½	5½	4¾	3½*	8½	6¾	5½	4¼
	100	0.58	7¾	6¼	5½	4¼	10½	8	6½	5
	200	0.65	9	7¼	6¼	5	12½	9¾	7¾	6
	400	0.75	11	8¼	7¼	5¾	14½	11½	9½	7
	800	0.85	13½	10	8½	6¾	17	13¾	11½	8½
KODAK TRI-X Pan Professional / TXT / 4164	80/160	0.52	4¼	3¾*	3¼*	2½*	5¼	4½	4	3*
	320	0.58	5	4½	4	3*	6½	5½	4¾	3½*
	640	0.65	6¼	5½	5	3¾*	8	6¾	6	4½
	1250	0.75	8	7¼	6½	4¾	10	8½	7½	5½
	2500	0.85	10	8¾	8	6	13	11	9½	7
KODAK T-MAX 400 Professional / TMY / 4053	100/200	0.52	6½	5½	5	3½*	8¼	6½	5½	4¼
	400	0.58	7½	6¼	5½	4	9¼	7½	6¼	4¾
	800	0.65	8½	7	6¼	4½	10½	8½	7	5¼
	1600	0.75	9¾	8	7	5¼	12	9½	8	6
	3200	0.85	11¼	9	8	6	13½	11	9½	7
KODAK EKTAPAN / PNT / 4162	25/50	0.52	4½	3½*	3*	2*	5½	4½	4	2½*
	100	0.58	6	5	4¼	3*	8	6½	5½	4
	200	0.65	7½	6½	5¾	4	10½	8¾	7½	5½
	400	0.75	10	8½	7½	5½	14	12	10½	7½
	800	0.85	13	11	9¾	7	17½	15½	14	10

* Development times shorter than 4 minutes may produce unsatisfactory uniformity.



Important

Development times shorter than 4 minutes may produce unsatisfactory uniformity.

TABLE 7: Processing Sheet Film with FRESH, DILUTE DEVELOPER (Development Times in minutes)

SHEET FILM	EI	CI	In Trays, DEVELOPER DILUTION												In Rotary-Tubes (with Continuous Agitation), DEVELOPER DILUTION											
			1:1				1:2				1:3				1:1				1:2				1:3			
			68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	68°F (20°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)
KODAK PLUS-X Pan Professional / PXT / 4147	32/64	0.52	7¼	6½	5	3¾*	8¾	8	6	5	10½	9½	7½	6	5	4½	3¼*	2½*	6	5½	4¼	3½*	7	6½	5¼	4
	125	0.58	8¼	7½	6	4¾	10¼	9½	7½	6	12½	11½	9	7	6¼	5½	4	3¼*	7¼	6½	5	4	8¼	7½	6¼	4¾
	250	0.65	10¼	9½	7½	6	13	12	9½	7¼	15¼	14	11	8½	7½	6¾	5	4	8½	7¾	6¼	5	10	9¼	7½	5¾
	500	0.75	13½	12½	10½	8	16¾	15½	12½	9½	19½	18	14½	11	10	9	6¾	5	11	10¼	8¼	6¼	14¼	13	9¾	7½
1000	0.85	19	17	13	10½	21¾	20	16	12	24¾	23	19	15	12½	11½	9	7	14	13	10½	8	19¼	17	12½	10	
KODAK T-MAX 100 Professional / TMX / 4052	25/50	0.52	9¼	8½	6½	5¼	12¾	11	8¼	6	15½	14½	11¾	9½	6¾	6½	5¾	5	9½	9	8	7	12¼	11½	10	9
	100	0.58	10½	9½	7½	6	13¾	12½	9¾	7¼	17¼	16	13	10½	7¾	7½	6¾	6	10½	10	9	8	13¾	13	11½	10½
	200	0.65	11½	10½	8½	7	15¼	14	11	8½	18¾	17½	14¼	11½	9	8½	7½	6¾	12	11½	10	9	16¼	15	13	11½
	400	0.75	13¼	12	9¾	8	17¼	16	12¾	9¾	21½	20	16¼	13	10½	9¾	8½	7½	14¼	13½	11½	10	20	18½	15¼	13
800	0.85	15¼	14	11¼	9	19¼	18	14½	11½	24¼	22½	18¼	14½	12	11½	10	8½	17	16	13½	11	24	22	17¾	14½	
KODAK TRI-X Pan Professional / TXT / 4164	80/160	0.52	7¾	7	5	3¾*	9¼	8½	6¾	5	12	11	8½	6	5¾	5	3¾*	2¾*	7½	6½	4¾	3¾*	8¼	7½	5½	4½
	320	0.58	9	8	6	4½	11½	10½	8	5¾	14¼	13	10	7	6¾	6	4½	3¼*	8¼	7½	5¾	4¼	10	9	6½	5¼
	640	0.65	10½	9½	7	5½	13½	12½	9½	7	16½	15	12	8¼	7¾	7	5½	3¾*	9½	8½	6½	5	11½	10½	7¾	6¼
	1250	0.75	13½	12	8½	6¾	17	15½	12	8¾	21	19	14½	10¼	9¾	9	6¾	4½	12	11	8	6	13¾	12½	9½	7¾
2500	0.85	17	15	10½	8	21	19	14½	10½	26½	24	17½	12½	12	11	8¼	5½	14¾	13½	10¼	7¼	17½	16	12	9¼	
KODAK T-MAX 400 Professional / TMY / 4053	100/200	0.52	9½	8½	6½	5½	11¼	10½	8½	7¼	14¾	13½	10½	8¾	7¼	6½	5¼	4¼	9½	8½	6¾	5¼	12½	11	8¾	7
	400	0.58	10½	9½	7¼	6	13	12	9½	8	16¼	15	11½	9¾	8¼	7¼	5¾	4¾	10½	9½	7½	5¾	14	12¼	9¾	7¾
	800	0.65	11¾	10½	8¼	6¾	14¾	13½	10½	8¾	17¾	16½	13	10¾	9¼	8¼	6¾	5¼	11¾	10¾	8½	6½	15½	13½	11	8½
	1600	0.75	13¼	12	9¼	7½	17	15½	12¼	10	20	19	15	12¼	10¾	9½	7¾	6	13¾	12½	10	7½	17¾	15½	12½	9¾
3200	0.85	15	13½	10½	8½	19	17½	13¾	11¼	23½	21½	17	14	12½	11	9	7	16	14½	12	8¾	20½	18	14½	11	
KODAK EKTAPAN / PNT / 4162	25/50	0.52	8	7	4½	2½*	10	9	6½	4¾	12¼	11	8½	6¾	5¼	4½	3½*	2¾*	6¼	5½	4¼	3½*	8	7	4¾	4
	100	0.58	9½	8½	6	3¾*	12	11	8½	6	14¼	13	10½	8½	7¼	6	4½	3¼*	7¾	7	5	4	10	8½	6	4½
	200	0.65	12¼	11	8	5½	15½	14	10½	7¾	18	16½	13	10½	9	7¾	5½	3¾*	9¾	8¾	6½	4¾	12	10½	7½	5½
	400	0.75	15½	14	10½	7½	19¾	18	14	10½	23½	21½	17	13¾	12	10	7	5	12½	11¼	8½	6	15	13½	10	7¼
800	0.85	19½	18	14¼	10½	24	22	18	13¾	28½	26	21	17	14¾	12½	9	6½	15	13¾	11	8	18¼	16½	12½	9½	

* Development times shorter than 4 minutes may produce unsatisfactory uniformity.

KODAK XTOL Developer

MORE INFORMATION

Kodak has many publications to assist you with information on Kodak products, equipment, and materials. The following publications are available from dealers who sell Kodak products, or you can contact Kodak in your country for more information.

E103CF	<i>Chemicals for KODAK Black-and-White Films (Matrix)</i>
F-7	<i>KODAK VERICHROME Pan Film</i>
F-8	<i>KODAK PLUS-X Pan and PLUS-X Pan Professional Films</i>
F-13*	<i>KODAK High Speed Infrared Film</i>
F-9	<i>KODAK TRI-X Pan and TRI-X Pan Professional Films</i>
F-10	<i>KODAK EKTAPAN Film</i>
F-32	<i>KODAK T-MAX Professional Films</i>
P-255	<i>KODAK Technical Pan Film</i>
Z-133E	<i>Monitoring and Troubleshooting KODAK Black-and-White Film Processes</i>
Y-30	<i>KODAK Plotting Form for Black-and-White Film Processing (20-sheet packages, CAT 176 9314)</i>

* Available via Faxback and on the Kodak website only.

For assistance in controlling processes, the following are available:

Z-133E	<i>Monitoring and Troubleshooting KODAK Black-and-White Film Processes</i>
	and
--	<i>KODAK Black-and-White Film Process Control Strips (CAT 180 2990)</i>
Y-30	<i>KODAK Plotting Form for Black-and-White Film Processing (20-sheet packages, CAT 176 9314)</i>

* Available via Faxback and on the worldwide web only.

Kodak Information Center's Faxback System

—Available 24 hours a day, 7 days a week—

Many technical support publications for Kodak products can be sent to your **fax** machine from the Kodak Information Center. Call:

U.S.A. 1-800-242-2424, Ext. 33
Canada 1-800-295-5531

If you have questions about KODAK PROFESSIONAL Products, call Kodak.

In the U.S.A.:
1-800-242-2424, Ext 19, Monday–Friday
9 a.m.–7 p.m. (Eastern time)

In Canada:
1-800-465-6325, Monday–Friday
8 a.m.–5 p.m. (Eastern time)

Or contact Kodak on-line at:
<http://www.kodak.com/go/professional>

Note: The products described in this publication may not be available in all countries. In countries other than the U.S., contact your local Kodak representative, or your usual supplier of Kodak products.



Kodak Professional Division
EASTMAN KODAK COMPANY

Kodak Professional