

# Three Sekonic Meters In One

[Sekonic L-718 Digi Master – Best Value in its Class]



54° Disc for  
Reflected Light  
Measuring Mode

Lumidisc for  
Incident and Flash  
Light Balance  
Measuring Mode

**in center**  
Lumisphere for  
Incident and Flash  
Measuring Mode

## Look at these impressive features:

- Receptor head rotates 270°, tilts up 90°, for maximum reading ease.
- Heavy duty rubberized sides assure positive non-slip holding.
- LCD Panel offers backlighting when working in dark surroundings.
- Displays digital and analog readouts.
- Incident and reflected measuring of ambient light or flash.
- Incident light balance measuring with Lumidisc, invaluable for photographing flat art and measuring individual lights in studio settings.
- Aperture, shutter priority or EV exposure mode.
- Digital readouts of f/stops in 1/10th increments.
- Digital readouts of battery capacity in 1/10th increments.
- Incident flash range f/1.4 to f/90 + 0.9.
- Cumulative multi-flash measurement.
- Cord or cordless flash measuring.
- Tripod socket permits placing meter on light stand in studio setting.
- Lock for continuous incident readings.
- Memory holds two exposure readings plus last measurement.
- Shutter speeds from 30 min. to 1/8000 sec.
- Flash shutter speeds 1 sec. to 1/500 sec.
- Cine speeds 8 to 128 FPS.
- Film speed range ISO 3 to 8000.

The L-718 is supplied with Lumisphere, Lumidisc and Reflecting Disc at **no extra charge**.

Comes with case, neck strap and batteries. Optional accessories are 5° Spot Attachment and Pinpoint Groundglass Probe.